

Contact us 800-892-3755

CustomerSupport@pioneermmagnetics.com

www.PioneerMVMagnetics.com

SWITCH INQUIRY FORM

Items marked by “ * ” are necessary.

Customer Information*

Today's Date

First Name

Last Name

E-Mail

Phone

Company

City/State/Province

Quote Due Date

Switch Preference*

- No Preference Powercon
- Schneider Siemens
- ABB Eaton

Switch Orientation*

- Left Side Right Side

Switch Size*

- 5KV, 600A 3Ø,3W, 60KV BIL, 40kAIC
- 15KV, 600A 3Ø,3W, 95KV BIL, 40kAIC
- 5KV, 1200A 3Ø,3W, 60KV BIL, 40kAIC
- 15KV, 1200A 3Ø,3W, 95KV BIL, 40kAIC

Enclosure*

- NEMA 1 NEMA 3R

Options

- 4" Diameter Infra-Red Window
- Kirk Key Interlocks

(Note: specify Kirk Key on transformer also)

Arrestors

Surge Arrestors (Set of 3)

- Distribution Class
- Intermediate Class
- Station Class
- None

Transformer Information*

- kVA
- Primary Voltage
- Secondary Voltage

Fusing*

Yes No

Fuse selection based on the transformer.

Rule of thumb: 1.33 X the self-cooled full load of the transformer.

Current Limiting CLE Fuses (5.5KV with Fuse Clips, Set of 3)

20E	25E	30E	40E
50E	65E	80E	100E
125E	150E	175E	200E
250E	300E	350E	400E
450E			

Current Limiting CLE Fuses (15.5KV with Fuse Clips, Set of 3)

• Indicates Double Barrel Fuses

20E	25E	30E	40E
50E	65E	80E	100E
125E•	150E•	175E•	200E•
250E•	300E•		

Options

- Fuse Clips (Set of 3)
- Double Barrel Fuse Clips (Set of 3)
- Blown Fuse Indicator Light
- Spare Fuse Pocket

Other Options:

- Thermostat Insulated Bus
- Strip Heater Auxiliary Switch
- Light Voltmeter
- Ammeter Porcelain Insulator
- Ground Ball Stud with Cover
- Current Transformer
- Potential Transformer
- Control Transformer

Notes/Special Requirements

FOR OFFICE USE ONLY

Part No _____ Quote No _____
 Quoted By _____ Date _____